



VOCAL MIC

OWNER'S MANUAL



Thank you for your purchase of this Sterling Audio[®] **P2** microphone. Designed for vocal performances, this mic captures the midrange clarity and full frequency response that vocalists, presenters and MCs demand.

KEY FEATURES

- Sterling Audio custom-tuned, vocal performance capsule.
- Dynamic capsule suspension for lowered handling noise and isolation in live performance environments.
- Cardioid polar pattern for off-axis noise rejection, and great SPL handling capability.
- Die-cast zinc body and reinforced grill for live performance environments.

CARE INSTRUCTIONS

- Never spray a cleaning agent on the microphone capsule itself, as moisture could potentially cause performance degradation.
- Avoid storing in temperatures above 100°F and below 40°F.
- Never disassemble your mic. There are no user serviceable parts inside.

SPECIFICATIONS

Microphone Type Handheld Vocal Mic
Transducer Type:Dynamic Moving Coil
Polar Pattern:Cardiod
Frequency Response:50Hz to 15kHz
Output Impedance:580Ω
Sensitivity:3.1 mV/Pa
Typical Load Impedance:>1000Ω
Product Length:7.0 inches (178mm)
Product Weight: 10.4 ounces (295g)

If you require assistance for customer support, please contact us.

Web Support: <u>https://sterlingaudio.net/contact-us/</u>

Phone Support: (888) 621-2154

Two (2) Year Limited Warranty

Subject to the limitations set forth below, Sterling Audio® hereby represents and warrants that the components of this product shall be free from defects in materials and workmanship, including implied warranties of merchantability or fitness for a particular purpose, subject to normal use and service, for two (2) years to the original owner from the date of purchase.

